

N1050 (4) NEUTRAL.

MAGNUM SAFETY SERIES

PERFORMANCE DATA:

» Total Solar Energy Rejected (Heat)	44%
» Visible Light Transmitted	48%
» Visible Light Reflected (External)	13%
» Ultra Violet Rejected	>98%
» Shading Coefficient	0.64
» SHGC	0.56
» U-Value – (W/m ² K)	5.68
» Glare Reduction	45%
» Solar Energy Reflected	12%
» Solar Energy Absorbed	140%
» Estimated Fade Reduction*	63%

BENEFITS:

- » W.E.R.S. Rating 2 Stars (cooling)/0.5 stars (heating).
- » Advanced sputtering technology.
- » Only stabilised metals used.
- » Manufactured to comply with Safety Glazing Standard AS/NZS2208 when applied to 3mm glass and above.
- » Almost three times thicker than normal film, increasing strength and safety features.
- » Original colour guaranteed to be long lasting.
- » Ideal where glass strengthening and good heat reduction are required.
- » Stops 44% of heat.
- » Over 98% of harmful UV rejected.
- » 4.5kg (10lb) pressure sensitive mounting adhesive.
- » Puncture strength 78 pounds force.
- » Ideal for glass upgrades.
- » Lifetime warranty residential - not transferable.
- » 12 year warranty commercial - not transferable.

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

Note: It is the sellers/installers responsibility to determine application & 'duty of care' requirements as required by building standards.



MEP FILMS
EST. 1985

LLUMAR • MADICO • SUN-GARD