

N1065 NEUTRAL.

SOLAR CONTROL SERIES

PERFORMANCE DATA:

» Total Solar Energy Rejected (Heat)	31%
» Visible Light Transmitted	63%
» Visible Light Reflected (External)	11%
» Ultra Violet Rejected	>98%
» Shading Coefficient	0.80
» SHGC	0.69
» U-Value – (W/m ² K)	5.68
» Glare Reduction	28%
» Solar Energy Reflected	9%
» Solar Energy Absorbed	30%
» Estimated Fade Reduction*	56%

BENEFITS:

- » Ideal for shop fronts and residential use.
- » Advanced sputtering technology.
- » Only stabilised metals used in production.
- » Clear appearance makes it ideal for display windows.
- » Good choice for use on coloured glass.
- » Stops 31% of heat.
- » Strengthens glass for added safety.
- » Over 98% of harmful UV rejected.
- » World's toughest scratch resistant surface.
- » Clear distortion free adhesive.
- » Lifetime warranty residential - not transferable.
- » 12 year warranty commercial - not transferable.

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.



MEP FILMS
EST. 1985

LLUMAR • MADICO • SUN-GARD