

# V28 SKY BLUE.

## SOLAR CONTROL SERIES

## PERFORMANCE DATA:

» Total Solar Energy Rejected (Heat)	65%
» Visible Light Transmitted	27%
» Visible Light Reflected (External)	34%
» Ultra Violet Rejected	>98%
» Shading Coefficient	0.39
» SHGC	0.35
» U-Value – (W/m <sup>2</sup> K)	5.84
» Glare Reduction	69%
» Solar Energy Reflected	33%
» Solar Energy Absorbed	45%
» Estimated Fade Reduction*	74%

## BENEFITS:

- » W.E.R.S. Rating 3.5 Stars (cooling).
- » Popular for use on commercial buildings.
- » Advanced sputtering technology.
- » Only stabilised metals used in production.
- » Manufactured guarantees colour long lasting.
- » Designed to work under extreme heat conditions.
- » Reduces 65% heat.
- » Reduces energy costs all year round.
- » Provides daytime privacy.
- » Good glare and fade reduction.
- » Strengthens glass for added safety.
- » Over 98% of harmful UV rejected.
- » World's toughest scratch resistant surface.
- » Neutral interior appearance.
- » Lifetime warranty residential - not transferable.
- » 12 year warranty commercial - not transferable.

Applied to 6mm clear glass

\* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.