

V38 SKY BLUE.

SOLAR CONTROL SERIES

PERFORMANCE DATA:

» Total Solar Energy Rejected (Heat)	56%
» Visible Light Transmitted	37%
» Visible Light Reflected (External)	27%
» Ultra Violet Rejected	>98%
» Shading Coefficient	0.50
» SHGC	0.44
» U-Value – (W/m ² K)	5.79
» Glare Reduction	58%
» Solar Energy Reflected	25%
» Solar Energy Absorbed	44%
» Estimated Fade Reduction*	69%

BENEFITS:

- » Popular for use on commercial buildings with clear laminated glass.
- » Advances sputtering technology.
- » Only stabilised metals used in production.
- » Manufacturer guarantees colour long lasting.
- » 56% heat rejection.
- » Reduces energy costs all year round.
- » Provides daytime privacy.
- » Good glare reduction.
- » Strengthens glass for added safety.
- » Over 98% of harmful UV rejected.
- » Good fade reduction.
- » World's toughest scratch resistant surface.
- » Clear distortion free adhesive.
- » Neutral interior appearance.
- » Lifetime warranty residential - not transferable.
- » 12 year warranty commercial - not transferable.

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.



MEP FILMS
EST. 1985

LLUMAR • MADICO • SUN-GARD